Plans for MTOR upgrade to full field in full volume

Mohamed Abdou, Alice Ying, Neil Morley

ALPS/PFC Meeting
Oakbrook, II, November 19, 2003




Some Specific Details on the Recent Experimental Study

section

The goal was to quantity the film height variation-

Width of the channel limited to about 7 cm if max B of 1.2 T is to be reached





manent



Why do we need/want larger volumes at high field in MTOR

PFC/ALPS/ALIST Module B MHD research

- Nearer term experiments needed to explore wide film flows for NSTX module B (competing effects of large aspect ratio films make this area unknown – HIMAG will be working on it soon)
- Nearer term experiments needed to explore closelyspaced jet array formation from common manifold systems in the relevant (high) magnetic field
- Large magnetic system for NSTX module B qualification and shakedown testing



How can we get high field over larger volume in MTOR?

- Current size of MTOR-NSTX LSM test article limited by the need of using iron flux concentrator
- We have been considering options for two years for how to operate at high field over large volumes
 - pulsed operation with liquid N2 cooled magnets
 - pulsed operation with arrays of batteries or capacitors
 - steady operation with addition of large amounts of iron closing more than ½ of the torus
 - steady operation with lab AC power upgrade and new power supply



What is needed for the preferred option of new power supply

Preface

Power upgrade to MTOR was proposed at last November meeting. However, it did not going forward due to a significant amount of money needed. The estimated total cost was > \$400 k, with a power upgrade to the lab of \$250k and a power supply of \$150 to 200 k.


What happened since then?

The E1 building at UCLA is to be torn down and the new Nanotechnology building replacing it will be switched to the 12.47 kV line, requiring a power trench down the alley right in front of our lab.

This provided an opportunity for us to bring the 12.47kV line into the lab. The cost was \$40k (in stead of \$250k) and we convinced the dean to pay the cost as an infrastructure upgrade.



2.5MW fusion power upgrade piggy-backed of Nanotech building project





Request Details

Now, it appears reasonable to ask for a power upgrade to MTOR (to run at its full capacity).

What do we need additionally?

12.47 KV termination box – above grade, north wall of 15-125

(\$40k, done)

Load Limiting Reactor Inductor

(optional, \$0k)

Full load Interrupter Switch

12.47kV to DC rectifying power supply

DC disconnect switch

All components integrated into Power supply unit, \$200k)


The biggest amount will be spent on the rectifier power supply, which transforms an input voltage of 12.47kV to an output current of 3664Adc (MTOR full coil current). The quote for this from the SatCon Power Systems Canada Ltd. is \$175.5k. There are other miscellaneous costs such as an ~\$20k for conduit and cable needed in the lab, and cooling system modifications



Power supply detail

2.75MW Thyristor Rectifier Power Supply

- Input Voltage: 12.47kV
- Output 3664Adc



• Integrated primary side LI switch







Request Details (Cont'd)

Specific Request

- It is requested that the \$200k needed for the rectifier power supply system to be shared and paid by the APEX unallocated fund and ALPS the discretionary money.
- A written request (document 3) has been provided to the ALPS SC for this purpose.
- For Fy2004 the proposed request is \$100k, while the remaining \$100k shall be provided in Fy2005. The upgrade will be spread over two years and completed in FY05

The absolute minimum bottom line

\$50 K from FY04 ALPS/PFC discretionary money (with assurance of similar funds in FY05)

